



A



2800-3000-3200-4000-5000



AXR / GXR



GENERAL FEATURES

- Compact size for storing and practical to use thanks to its vertical design
- Simple to transport horizontally in the car
- **Comet AXR pump with brass head and ceramic pistons (on KA 2800 GXR pump with brass head and stainless steel pistons)**
- Pressure gauge
- Built-in professional unloader valve
- **EASY-START** device on single-phase models
- **TotalStop** device
- Rotary switch
- Regulated low-pressure detergent suction
- Motor thermal protection



CARATTERISTICHE GENERALI

- *Ingombro ridotto nella messa a riposo e praticità d'uso in condizioni di lavoro grazie allo sviluppo verticale*
- *Semplicità di trasporto su auto in posizione orizzontale*
- *Pompa Comet AXR con testata in ottone e pistoni in ceramica (su KA 2800 pompa GXR con testata in ottone e pistoni in acciaio)*
- *Manometro pressione*
- *Valvola di regolazione professionale integrata*
- *Dispositivo EASY-START sui modelli monofase*
- *Dispositivo TotalStop*
- *Interruttore rotativo*
- *Aspirazione detergente in bassa pressione con regolazione*
- *Protezione termica del motore*
- *Usa semiprofessionale gravoso*

- Adjustable detergent suction device from an external tank with filter
- Dispositivo di aspirazione detergente da tanica esterna, regolabile con filtro

- 3 lt detergent tank, easily removed
- Serbatoio detergente 3 lt facilmente rimovibile

- Comet AXR/GXR pump, 3 axial plungers and brass pump head
- Pompa Comet AXR/GXR, 3 pistoni assiali e testata in ottone






- 15 m hose reel. Practical handle and stop device
- Avvolgitubo di 15 m. Comoda maniglia e dispositivo di fermo



CODE CODICE	MODELS MODELLI	MOTORPUMP MOTOPIOMPA												
			Ph	V	Hz	bar	MPa	l/h	HP	kW	kW	l	kg	(L x W x H) cm
90371147	A2800MClassic	GXR	1	230	50	140	14	540	2,6	1,9	2,6	3,0	36	44 x 42 x 94
90371002	A3000MClassic	AXR	1	230	50	130	13	720	3,0	2,2	2,9	3,0	36	44 x 42 x 94
90371001	A3200MClassic	AXR	1	230	50	150	15	600	3,0	2,2	2,9	3,0	36	44 x 42 x 94
90371005	A5000TClassic	AXR	3	400	50	200	20	720	5,0	3,7	4,3	3,0	36	44 x 42 x 94
90371148	A2800MExcel	GXR	1	230	50	140	14	540	2,6	1,9	2,6	3,0	36	44 x 42 x 94
90371021	A3000MExcel	AXR	1	230	50	130	13	720	3,0	2,2	2,9	3,0	36	44 x 42 x 94
90371012	A3200MExcel	AXR	1	230	50	150	15	600	3,0	2,2	2,9	3,0	36	44 x 42 x 94
90371016	A4000TExcel	AXR	3	400	50	170	17	720	4,3	3,2	3,8	3,0	36	44 x 42 x 94
90371019	A5000TExcel	AXR	3	400	50	200	20	720	5,0	3,7	4,3	3,0	36	44 x 42 x 94



STANDARD ACCESSORIES > DOTAZIONE STANDARD

CLASSIC		EXCEL	
	GC 251 gun with protection <i>Pistola GC 251 con protezione</i>		
	Lance with adjustable jet, with nozzle (for the A 2800 model only) <i>Lancia getto regolabile con ugello (solo per modello A2800)</i>		
	Bent lance with detergent head, without nozzle <i>Lancia angolata con testina detergente, senza ugello</i>		
	Fan shape nozzle 1/4" MEG connection <i>Ugello con getto a lama attacco 1/4" MEG</i>		
	8 m rubber delivery hose kit <i>Kit tubo gomma mandata 8 m</i>		15 m rubber delivery hose kit (on Hose Reel) <i>Kit tubo mandata 15 m (su Avvolgitubo)</i>